

螺纹千分尺量杆 167系列 MB (螺纹千分尺用)

●用于调整螺纹千分尺基准点。



167-264
MB-100 (60°螺纹)



167-262
MB-50 (60°螺纹)

货号	型号	长度(mm)	极限偏差(μm)
公制型(统一) θ = 60°			
167-261	MB-25(60°螺纹)	25	±4
167-262	MB-50(60°螺纹)	50	±5
167-263	MB-75(60°螺纹)	75	±6
167-264	MB-100(60°螺纹)	100	±7
167-265	MB-125(60°螺纹)	125	±8
167-266	MB-150(60°螺纹)	150	±9
167-267	MB-175(60°螺纹)	175	±10
167-268	MB-200(60°螺纹)	200	±11
167-269	MB-225(60°螺纹)	225	±12
167-270	MB-250(60°螺纹)	250	±13
167-271	MB-275(60°螺纹)	275	±14
惠氏型 θ = 55°			
167-272	MB-25(55°螺纹)	25	±4
167-273	MB-50(55°螺纹)	50	±5
167-274	MB-75(55°螺纹)	75	±6
167-275	MB-100(55°螺纹)	100	±7
167-276	MB-125(55°螺纹)	125	±8
167-277	MB-150(55°螺纹)	150	±9
167-278	MB-175(55°螺纹)	175	±10
167-279	MB-200(55°螺纹)	200	±11
167-280	MB-225(55°螺纹)	225	±12
167-281	MB-250(55°螺纹)	250	±13
167-282	MB-275(55°螺纹)	275	±14

V型测砧千分尺量杆 167系列 MB(V型测砧千分尺)

●用于调整V型测砧千分尺的基准点。



167-329
MB-25

货号	型号	长度(mm)	极限偏差(μm)	类型
167-327	MB-5	5	±2	柱塞
167-328	MB-10	10		
167-329	MB-25	25		
167-330	MB-40	40	±3	环套
167-331	MB-55	55		
167-332	MB-70	70		
167-333	MB-85	85		
167-334	MB-100	100	±5	环套
167-335	MB-115	115		
167-336	MB-130	130		